


Job Name:

System Reference: Date:



SIMPLE MA REMOTE CONTROLLER (PAC-YT53CRAU-J) SPECIFICATIONS

- · Controls group operation for up to 16 indoor units in a single group
- · Supports both Fahrenheit and Celsius
- User defined functions:
 - ON/OFF
 - Operation mode: AUTO (R2-Series only), COOL, HEAT, FAN, DRYING, or SETBACK
 - Set temperature
 - Fan speed setting
 - Air flow direction
 - Set temperature range: 40°F to 95°F depending on operation mode and indoor unit connected.
- Set temperature range limit: Simple MA allowable set temperature range can be reduced for cool and heat modes.
- LOSSNAY®: Simple MA for interlocked system can set high/low/Stop on LOSSNAY.
- Room temperature can be sensed either at the indoor unit (default) or at the remote controller.
- Diagnostics: Displays four-digit error code and error unit address.
- Grouping: Same group use only with other PAC-YT53CRAU-J Simple MA Controllers, PAR-33MAA-J Deluxe MA Remote Controllers, and PAR-FL/A32MA Wireless MA Remote Controllers with up to two remote controllers per group.
- · Addressing: No addressing required.
- Wiring: Uses two-wire, stranded, non-polar control wire for connecting TB15 connection terminal on the indoor unit.
- · Requires crossover wiring for grouping across indoor units.
- Dimensions: 2-3/4 x 9/16 x 4-3/4" (70 x 14.5 x 120mm).



System example

NOTES:

DIMENSIONS: PAC-YT53CRAU-J

